

Semi Synthetic PLUS SAE 10W-30 Motor Oil

Petromerica Semi Synthetic PLUS SAE 10W-30 Motor Oil is a premium quality multi-grade motor oil designed with a state-of-the-art low friction additive system for superior engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Petromerica Semi Synthetic PLUS Motor Oil is recommended for passenger car, truck, sport utility vehicle and other mobile or stationary engines.

Petromerica Semi Synthetic PLUS SAE 10W-30 Motor Oil meets or exceeds ILSAC GF-5 and American Petroleum Institute (API) Resource Conserving SN PLUS service classifications and is compatible with all prior API categories. Petromerica Semi Synthetic PLUS SAE 10W-30 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including ACEA A1/B1 & A5/B5, Ford WSS-M2C205A, GM 6094M, Chrysler MS6395, and many other OEM's specifications where a semi synthetic API SN motor oil is recommended.

Benefits and Applications

- Lower pour point reduces start-up wear during cold weather
- Enhanced oxidative stability, emission system and wear protection
- · Semi synthetic oil helps to improve fuel economy
- Superior resistance to sludge and varnish deposit formation

10W-30 Typical Characteristics - V191202

| SAE GRADE | Syn Blend | 10W-30 |
|------------------------|------------|--------------|
| API SERVICE | | SN PLUS/GF-5 |
| API Gravity | ASTM D287 | 32.6 |
| Flash Point, COC °C/°F | ASTM D92 | 237 / 458.6 |
| Pour Point, °C/°F | ASTM D97 | -39 / -38.2 |
| Viscosity @ 40°C, cSt | ASTM D445 | 64.15 |
| Viscosity @ 100°C, cSt | ASTM D445 | 10.08 |
| Viscosity Index | ASTM D2270 | 143 |
| CCS, mPa-sec °C max | ASTM D5293 | 7000 @ -25 |
| Total Base No. TBN | ASTM D2896 | 7.5 |

Typical test data are average values only. Minor variations, which do not affect performance, may occur.

API SN PLUS ILSAC GF-5

ACEA A1/B1 & A5/B5, Ford WSS-M2C205A, GM 6094M, Chrysler MS6395







Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information, data or products can be used without infringing patents of third parties.