

Technical Product Information
 www.usglobalpetroleum.com
 www.everestoil.com
 773-376-9660

DEXRON
 APPROVED
 License Number: J-60189

Premium
 Performance

EVEREST[®]

Full Synthetic Automatic Transmission Fluid

Everest DEXRON[®]-VI Full Synthetic Automatic Transmission Fluid is a fully licensed DEXRON[®]-VI ATF (License Number: J-60189), the only GM[®] approved specification for vehicles of model years 2006 and newer. Everest Multi-Vehicle DEXRON[®]-VI ATF is a high performance universal ATF providing superior oxidation control, extended service intervals, maximum year-round low and high temperature performance, improved fuel economy and shear stability. It is suitable for use where GM DEXRON[®]-VI, DEXRON[®] III/III(H)/IIE, DEXRON[®] II, Ford MERCON[®] LV, Allison[®], Honda[®] Z-1, Hyundai/Kia SP-II/III/IV, Toyota WS,T-III, T-IV, Mercedes Benz[®], or Nissan[®] Matic C/D/J/K/S Fluids are recommended.

*Not for used in extended drain heavy duty diesel, Type F, CVT or DCT applications.

Approvals, Applications and Benefits

- GM DEXRON[®], DEXRON[®] II, II-E, III, III-G, III-H, VI • Ford MERCON[®], MERCON[®] LV • Acura ATF-Z1 • Audi 5 HP LT71141
- Chrysler (Mopar) ATF-Plus, ATF +3, ATF +4 • Allison C-3, C-4, TES-295, TES-389 • CAT TO-2 • Daewoo LT 71141 • Esso LT 71141
- BMW • Honda Z-1 • Hyundai/Kia SP-II/III/IV • JASO • FIAT T-IV type, JWS 3309 • Jaguar ATF 3403 M115, ATF LT71141, ZF 5HP24
- ISUZU BESCO ATF-II /III • Mazda ATF D-II/M-III/M-VFZ/S-1/N-1 • MINI COOPER T-IV • Opel (all vehicles) • Peugeot ZF 4HP20
- Mercedes • Mitsubishi • Nissan/ Infinity Matic Fluids • Toyota ATF D-II/D-III/T-III/T-IV/WS • VW 5 HP, G-055-025 A2 (JWS 3309)
- Porsche ZF 5HP19FL, ZF 5HP20, LT71141 • Saab T-IV • Scion (all vehicles) • Shell 3403, M115, LA 2634 • Subaru ATF • Suzuki ATF
- Vickers M2950-S, I-286-S • Voith • Volvo CE 97340 • ZF all 3 & 4 speed transmission • and many more
- Superior all-temperature, year-round protection and high performance
- Advanced anti-wear protection and shear stability
- Smoother shifting, protection against shudder
- Extended life of service and performance

Typical Characteristics - Dexron[®] VI V190619

GRADE	Test Method	DEXRON [®] -VI
Color	Visual	Red
Viscosity @ 100°C, cSt	ASTMD 445	5.8
Viscosity @ 40°C, cSt	ASTMD 445	29.5
Viscosity Index	ASTMD 2270	145
Pour Point, °C/°F	ASTMD 97	-51/ -59.8
Flash Point, COC °C/°F	ASTMD 92	220/ 428
API Gravity	ASTMD 1298	36.0
Brookfield Vis.cP @ -40°C	ASTMD 2983	10,000

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

Suitable for:

GM DEXRON[®]-VI, DEXRON[®] III/III(H)/IIE, Nissan[®] Matic Fluids, Hyundai/Kia SP-II/III/IV, Toyota WS, T-III, T-IV, Ford MERCON[®] LV, Mercedes Benz[®], Honda[®] Z-1, Allison[®] C-3, C-4, Volvo CE 97340, ZF TE-ML 09X



HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.