

Technical Product Information
 www.usglobalpetroleum.com
 www.everestoil.com
 773-376-9660

LV ATF HP

*Premium
 Performance*

EVEREST®

Full Synthetic Automatic Transmission Fluid

EVEREST Full Synthetic LV ATF HP is a high performance full synthetic Automatic Transmission Fluid that is used in modern powerful vehicles requiring DEXRON® HP ATF. It meets the standard of General Motors making it a suitable replacement for a variety of GM parts, including GM Part 19355656, 95599825 and 19417577. It is formulated from 100% synthetic base oils and an advanced additive system that delivers extended transmission life and improve overall transmission durability and cleanliness while providing smooth gear shifting during all operating conditions. Its high viscosity index helps to protect your transmission against thermal breakdown at high operating temperatures, its low-temperature fluidity provides outstanding performance at extremely low ambient temperatures. Everest Full Synthetic LV ATF HP is suitable for use where GM DEXRON®-VI, DEXRON® III/III(H)/IIE, DEXRON® II, Ford MERCON® LV, Allison®, Honda® Z-1, Hyundai/Kia SP-II/III/IV, Toyota WS,T-III, T-IV, Mercedes Benz®, BMW 1375.4, KIA SPIVM, VAG G055540A2, Nissan® Matic Fluids are recommended.

- All operating conditions and a wide range of temperatures
- Compatible with mineral ATF fluids and all common seal materials
- Outstanding long-term frictional properties
- Exceptional thermal and oxidation stability
- Outstanding film-strength and anti-wear properties
- Excellent low-temperature fluidity

Typical Characteristics - LV ATF HP

GRADE	Test Method	LV ATF HP
Color	Visual	Red
Viscosity @ 100°C, cSt	ASTMD 445	5.7
Viscosity @ 40°C, cSt	ASTMD 445	27
Viscosity Index	ASTMD 2270	152
Pour Point, °C/°F	ASTMD 97	-54 / -65.2
Flash Point, COC °C/°F	ASTMD 92	233 / 451.4
API Gravity	ASTM D287	36
Brookfield Vis.cP @ -40°C	ASTMD 2983	8,000

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

**Meets the
 standard of**
 General Motors for
 DEXRON® HP ATF
 DEXRON®-VI,
 DEXRON®
 III/III(H)/IIE



V190719



HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.