



Chain Oil

Specifications:

<i>Property</i>	<i>Light 342CL32XB-</i>	<i>Medium 342CM68XB-</i>	<i>Heavy 342CH11XB-</i>
<i>Kinematic Viscosity @ 40°C, cSt</i>	33.6	71.5	121.7
<i>Specific Gravity @ 15.6°C (60°C)</i>	0.855	0.865	0.874
<i>Color</i>	Red	Red	Red
<i>Pour Point, °C</i>	-33	-27	-12
<i>Flash Point (COC), °C</i>	202	224	236

NOTE: Typical values shown above are representative of current production and may vary within modest ranges.

Performance / Applications:

- *contains a tackiness additive which reduces throw-off and drippage from moving parts such as chainsaw chains while minimizing wear of moving parts.*
- *all 3 grades are red in color for visual confirmation of oil presence in applications such as:*
 - Chainsaw chain lubrication*
 - Drive chains / chain conveyors*
 - Gear boxes requiring a tacky oil*

Typical test data are average values only. Minor variations, which do not affect performance, may occur.

MADE IN 
THE U.S.A.

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (MSDS) Material Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.